

CURB STOP/SWING CHECK VALVES

PP/PVC
PP/316 SS

DESCRIPTION

Polypropylene Curb Stop / PVC or 316 SS Swing Check Assemblies for PE/PVC pressure piping applications.

TUBE

IPS(OD) For use on HDPE Pipe SDR 7.3 thru SDR 17 (Sizes 1-1/4" - 2")
For use on Sch 40/80 PVC Pipe with SS Gripper Ring (Sizes 1-1/4" - 2")

CTS(OD) For use on Certified PE Pipe SDR 9 & SDR 11 (Sizes 1-1/4" - 2")
For use on Cross Linked Pipe PE SDR 9 for Cold Water Only. (Sizes 1-1/4" - 2")

WORKING PRESSURE

PP Curb Stop / PVC Check Valve at 73° F (23° C) curb stop rated to 200 PSI,
swing check rated to 125 PSI
PP Curb Stop / 316 SS Check Valve at 73° F (23° C) 1-1/4" - 2" rated to 200 PSI

FEATURES

Compression (IPS & CTS) & FIPT end connectors available
Curb Stop handle has built in torque overload protection (ratcheting handle)
Check Valves available in PVC or 316 SS
No Inserts Required
Fully Serviceable
EPDM O-Rings
Color coded
Curb Stop is UV stabilized
Pre-assembled prior to leaving factory
ISO 9001 certified

APPLICATIONS

Low Pressure Sewer



1-1/4" IPS PP CURB STOP/PVC SWING CHECK ASSEMBLY



1-1/2" IPS PP CURB STOP/SS SWING CHECK ASSEMBLY